



12 Ton Capacity Hand Pump Operated Shop Press

INTENDED USE

Straightening, bending & pressing.
Removing & installing gears,
bearings & bushings.



- Manual pump power unit with "Parkerized" pump piston, ram and extension screw to inhibit rust from entering the hydraulic system.
- Pair of bed plates included.
- Shielded heavy duty ram return springs.
- Power unit is bearing mounted for horizontal movement on head channel.
- Zero distortion, heavy duty structural steel frame.
- Optional equipment below can be used on model 78022D press. Model 78000 arbor plates and model 78032 bearing puller below can be used on model 78013A press.

MODEL NUMBER		RAM TRAVEL	THROAT HEIGHT		THROAT BED HEIGHT		BETWEEN	BETWEEN	BASE		OVERALL	SHIPPING WEIGHT
	CAPACITY		MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	(Lbs.)
78013A	12 Ton	5.875"	5"	38.25"	25"	8 x 4.75"	5"	6"	34"	28"	70.625"	266





20 Ton Capacity Hand Pump Operated Shop Press

INTENDED USE

Straightening, bending & pressing. Removing & installing gears, bearings & bushings.



- Manual pump power unit with "Parkerized" pump piston, ram and extension screw to inhibit rust from entering the hydraulic system.
- Pair of bed plates included.
- Shielded heavy duty ram return springs.
- Power unit is bearing mounted for horizontal movement on head channel.
- Zero distortion, heavy duty structural steel frame.

MODEL NUMBER		RAM	THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	SHIPPING WEIGHT	
١	NUMBER	CAPACITY	TRAVEL	MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	(Lbs.)
1	78022D	20 Ton	6.625"	7.125"	35.5"	30"	7 x 4.75"	6"	7"	40"	28"	70.625"	394



78024

25 Ton Capacity Air / Hydraulic Pump Operated Shop Press

INTENDED USE

Straightening, bending & pressing.
Removing & installing gears,
bearings & bushings.



- Air/hydraulic foot pump (Model 910130A) provides hands free operation.
- Pair of bed plates included.
- Self-retracting ram can slide for horizontal movement on head channel.
- Zero distortion, heavy duty structural steel frame.
- Liquid filled gauge measures ram force and internal working pressure.

MODEL NUMBER		RAM TRAVEL	THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	SHIPPING WEIGHT
	CAPACITY		MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	(Lbs.)
78024	25 Ton	8"	6.75"	40"	30.5"	8 x 4.75"	6"	7"	40"	28"	76.75"	430





50 Ton Capacity Hand Pump Operated Shop Press

INTENDED USE

Heavy duty use in truck garages and industrial work shops.



- Manually operated two speed pump provides quick ram travel to load.
- Safety overload system protects power unit.
- Hand operated winch raises and lowers press bed.
- Liquid filled gauge measures ram force in pounds and tons.
- Self-retracting ram is bearing mounted for lateral movement on head channel.

Γ	MODEL		RAM	THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	CHIDDING
١	NUMBER	CAPACITY	TRAVEL	MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	SHIPPING WEIGHT
	78055A	50 Ton	6.25"	7.5"	32.625"	34.5"	7 x 5"	5.625"	7.375"	50"	40"	72.75"	804 lbs.





50 Ton Capacity Air / Hydraulic Pump Operated Shop Press

INTENDED USE

Heavy duty use in truck garages and industrial work shops. Equipped with an air/hydraulic foot pump and model 910036A 10' hose.



- Equipped with high speed air/hydraulic foot pump.
- Safety overload system protects power unit.
- Hand operated winch raises and lowers press bed.
- Liquid filled gauge measures ram force in pounds and tons.
- Self-retracting ram is bearing mounted for lateral movement on head channel.

MODEL	MODEL		THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	SHIPPING
NUMBER	CAPACITY	RAM TRAVEL	MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	WEIGHT
78057A	50 Ton	6.25"	7.5"	32.625"	34.5"	7 x 5"	5.625"	7.375"	50"	40"	72.75"	801lbs.
78077	50 Ton	13.25"	7.5"	32.625"	34.5"	7 x 5"	5.625"	7.375"	50"	40"	72.75"	833 lbs.





50 Ton Capacity Electro / Hydraulic Pump Operated Shop Press

INTENDED USE

Heavy duty use in truck garages and industrial work shops. Equipped with model 910052A electro/hydraulic foot pump and model 910036A 10' hose.



- Equipped with high speed air/hydraulic foot pump.
- Safety overload system protects power unit.
- Hand operated winch raises and lowers press bed.
- Liquid filled gauge measures ram force in pounds and tons.
- Self-retracting ram is bearing mounted for lateral movement on head channel.

MODEL	MODEL		THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	SHIPPING
NUMBER		RAM TRAVEL	MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	WEIGHT
78058A	50 Ton	6.25"	7.5"	32.625"	34.5"	7 x 5"	5.625"	7.375"	50"	40"	72.75"	814 lbs.
78078	50 Ton	13.25"	7.5"	32.625"	34.5"	7 x 5"	5.625"	7.375"	50"	40"	72.75"	846 lbs.





100 Ton Capacity Electro / Hydraulic Pump Operated Shop Press

INTENDED USE

Heavy duty use in truck garages and industrial work shops. Equipped with model 910019B electro/hydraulic foot pump and model 910036A 10' hose.



- Equipped with high speed electro/hydraulic foot pump.
- Safety overload system protects power unit.
- Hand operated winch raises and lowers press bed.
- Liquid filled gauge measures ram force in pounds and tons.
- Self-retracting ram is bearing mounted for lateral movement on head channel.

Γ	MODEL		RAM	THROAT HEIGHT		THROAT	BED HEIGHT	BETWEEN	BETWEEN	BASE		OVERALL	CLUDDING
١	NUMBER	CAPACITY	TRAVEL	MIN.	MAX.	WIDTH	ADJUSTMENTS	UPRIGHTS	BED RAILS	WIDTH	DEPTH	HEIGHT	SHIPPING WEIGHT
١	78110C	100 Ton	10.25"	18.25"	45.75"	40.25"	8 x 4.5"	5.625"	9"	58"	40"	81"	1,777 lbs.